


GB

LOADER L5



www.ecomega.com

ECOMEGA L5 LARGE GIANT TIRE is a high ply bias tire design to maximize life time and operating hours in severe rock applications. Excellent cut and tear resistance. Extra deep tread and rugged casing for rough terrain. ECOMEGA bias giant L5 are built to perform in everything from soft underfoot conditions to severe shot rock environments. The thick nylon casings resists cuts and bruises and provides also retreadability.

The solid centreline section provides long wear and a smooth ride and is ideal for high torque applications and hard rock quarry service.

Ω ECOMEGA®
ECOLOGICAL NATURAL RUBBER

Ω ECOMEGA[®] LOADER L5

ECOLOGICAL NATURAL RUBBER

SIZE	PR	TREAD PATTERN	TREAD DEPTH (mm)	RIM SIZE	TUBE TYPE	INFLATED DIMENSIONS (mm)			MAX LOAD (kg) VERSUS SPEED			RELATIVE INFLATION PRESSURE (kPa)		
						OD	SW		10 Km/h	50 Km/h	50 Km/h	10 Km/h	50 Km/h	50 Km/h
35/65-33	30	L-5	100	28.00 / 3.5	TBLS	2.077	890		21.800	12.600		450	300	
35/65-33	42	L-5	100	28.00 / 3.5	TBLS	2.077	890		26.500	15.300		625	625	
45/65-45	58	L-5	100	36.00 / 4.5	TBLS	2.733	1.140		50.000	-		675	-	

REMARKS

Consult tyre and wheel manufacturer for confirmation of the suitability of the tyre / rim combination particularly with regard to rim profile, wheel strength and maximum inflation pressure. The sizes given are according to ETRTO or TRA, where available. For exact sizes, please consult the technical department. Creep speed is a travel rate of not over 60 m in a 30 minute period.

