

GB

PREMIUM PM SOLID



ECOMEGA PREMIUM PM solid tire generation is an innovative tire developed for the most exigent customer applications.

The tire style make it very nice and aggressive in the looking, the body of the casing very tough, the pattern design and the bigger tread surface improve stability and load dispersion in the ground. Built with a multi-layered natural rubber compound, the system of three different rubber types assures the maximum elasticity and comfort, reduce rolling resistance and push for a higher working life. Moreover the low heat build up, the improved traction guarantee a high stability and a very long service hours are guarantee.

Sidewalls have been strongly reinforced to protect the tire from lateral damages. Available also in no marking version and in easy-mount or fast/clip version to be fitted in rims without locking

www.ecomega.com

Ω ECOMEGA®
ECOLOGICAL NATURAL RUBBER

ECOMEGA[®] PREMIUM PM SOLID

ECOLOGICAL NATURAL RUBBER

Immagine Associati

TYRE SIZE	RIM SIZE	TYRE WIDTH ± 2% (mm)	OUTSIDE DIA. ± 2% (mm)	TREAD WIDTH ± 1% (mm)	INSIDE DIA. ± 1% (mm)	TYRE WT (Kg)	Forklift Load Capacity			
							LBS AT 16 MILES/HR		KGS AT 25 KM/HR	
		at Base					LOAD WHEEL	STEER WHEEL	LOAD WHEEL	STEER WHEEL
4.00-8	2.50-8	in progress	-	-	-	-	-	-	-	-
* 4.00-8	3.00-8	in progress	-	-	-	-	-	-	-	-
4.00-8	3.75-8	in progress	-	-	-	-	-	-	-	-
* 5.00-8	3.00 D-8	121	445	121	194	15,9	3.120	2.405	1.415	1.090
* 15x4 1/2-8	3.00-8	108	377	106	198	10,0	2.295	1.765	1.040	800
* 16x6-8	4.33-8	151	412	135	198	15,8	2.800	2.150	1.270	975
* 18x7-8	4.33-8	152	453	136	197	21,1	4.730	3.640	2.145	1.650
* 140/55-9	4.00-9	in progress	-	-	-	-	-	-	-	-
* 6.00-9	4.00-9	138	519	119	218	25,7	4.155	3.195	1.885	1.450
* 21x8-9	6.00-9	185	513	165	220	34,0	6.075	4.675	2.755	2.120
* 6.50-10	5.00-10	161	561	138	243	34,1	5.160	3.970	2.340	1.800
* 200/50-10	6.50-10	193	456	169	243	25,1	5.445	4.190	2.470	1.900
* 23x9-10	6.50-10	200	580	175	243	47,3	6.965	5.355	3.160	2.430
* 150/100-13	3.75-13	in progress	-	-	-	-	-	-	-	-
* 7.00-12	5.00-12	166	650	151	297	47,2	6.435	4.940	2.920	2.240
* 23x10-12	8.00-12	234	594	214	293	53,9	8.311	6.393	3.770	2.900
* 27x10-12	8.00-12	247	675	220	294	77,0	8.600	6.615	3.900	3.000
* 7.00-15	5.50-15	173	702	162	377	53,4	7.815	6.005	3.545	2.725
* 7.50-15	6.00-15	in progress	-	-	-	-	-	-	-	-
* 8.15-15 (28x9-15)	7.00-15	214	694	195	376	61,3	7.595	5.840	3.445	2.650
* 8.25-15	6.50-15	211	809	187	375	92,4	10.470	8.045	4.750	3.650
* 250-15	7.00-15	223	723	199	377	70,5	10.460	8.045	4.745	3.650
* 250-15	7.50-15	in progress	-	-	-	-	-	-	-	-
* 7.50-15	6.50-15	206	761	185	376	77,2	-	-	-	-
* 300-15	8.00-15	256	800	226	377	111,8	12.895	9.920	5.850	4.500
* 28x12.5-15	9.75-15	in progress	-	-	-	-	-	-	-	-
* 355/65-15	9.75-15	in progress	-	-	-	-	-	-	-	-
9.00-20	6.50-20	in progress	-	-	-	-	-	-	-	-
9.00-20	7.00-20	in progress	-	-	-	-	-	-	-	-
10.00-20	7.50-20	in progress	-	-	-	-	-	-	-	-
10.00-20	8.00-20	in progress	-	-	-	-	-	-	-	-
12.00-20	8.00-20	in progress	-	-	-	-	-	-	-	-
12.00-20	8.50-20	in progress	-	-	-	-	-	-	-	-
12.00-20	10.00-20	in progress	-	-	-	-	-	-	-	-
12.00-24	8.50-24	in progress	-	-	-	-	-	-	-	-
14.00-24	10.00-24	in progress	-	-	-	-	-	-	-	-

* Clip/Fast version available

REMARKS
Consult tyre and wheel manufacturer for confirmation of the suitability of the tyre / rim combination particularly with regard to rim profile, wheel strength and maximum inflation pressure. The sizes given are according to ETRTO or TRA, where available. For exact sizes, please consult the technical department. Creep speed is a travel rate of not over 60 m in a 30 minute period.



Modification Reserved